


DOCKER 85

GUARDRAIL EXMDS

RANGE : MOBILE SCAFFOLD TOWERS / MATERIAL : ALUMINIUM / MAX HEIGHT : 13,90 M
AVAILABLE IN 3 LENGTHS : 2,05 / 2,54 / 2,95 M

WITH ITS HIGH MANOEUVRABILITY,
LIGHTNESS AND SAFETY, THE DOCKER 85
OFFERS INCREASING TECHNICAL PROWESS

VIDÉOS :



SCAN



duarib.pro/d2



INTEGRATED DIFFERENCE -
IN-HEIGHT SET-UP



- Maxi difference in level setup:1,50 m

DOCKER150 WIDHT 1,50 M:
LARGE WORK AREAS AT LEVELS



	D85 - LENGHT 2,05 M	D85 - LENGHT 2,54 M	D85 - LENGHT 2,95 M
Material	Aluminium	Aluminium	Aluminium
Assembly type	Welded	Welded	Welded
Ø uprights	Ø 45 mm	Ø 45 mm	Ø 45 mm
Work heights	From 3,90 m to 13,90 m	From 3,90 m to 13,90 m	From 3,90 m to 13,90 m
Uprights spacing size	Length 2,05 x Width 0,85 m	Length 2,54 x Width 0,85 m	Length 2,95 x Width 0,85 m
Overall size	Lenght 2,17 x Width 0,96 m	Lenght 2,66 x Width 0,96 m	Lenght 3,07 x Width 0,96 m
Platform	- Aluminium/wooden platform, double trapdoor, integrated aluminium toe-boards - Usable area : 1,95 x 0,60 m - Load capacity per platform: 232 Kg	- Aluminium/wooden platform, double trapdoor, integrated aluminium toe-boards - Usable area : 2,44 x0,60 m - Load capacity per platform: 292 Kg	- Aluminium/wooden platform, double trapdoor, integrated aluminium toe-boards - Usable area : 2,85 x 0,60 m - Load capacity per platform: 340 Kg
Adjustable wheels	Ø 200 mm, wheels-height adjustment screw adjustable over 20 cm	Ø 200 mm, wheels-height adjustment screw adjustable over 20 cm	Ø 200 mm, wheels-height adjustment screw adjustable over 20 cm
Safety 3 ★	Decree 2004-924 Standard NF EN 1004	Decree 2004-924 Standard NF EN 1004	Decree 2004-924 Standard NF EN 1004

MADE IN
FRANCE