

TELETOWER

◦ LENGTH : 1,50 M
Max working height : 4 m

COMPLIANT WITH
FRENCH REGULATION

DECREE 2004-924

TELESCOPIC SCAFFOLD TOWER 7 WORKING HEIGHTS

EXCLUSIVE ASSETS

COMPACT DIMENSIONS



- Compact folded dimensions for easy storage and transport (Height 1.10m - Width 0.80m Thickness 0.45 m).
- Transportable in small van or estate car.



- Structure, folded platform and toe boards are all included in the trolley.
- No spare parts.

EASY TO ERECT



- Fully erected in under 3 minutes by one person : a simple and effortless operation.
- Low space requirements for installation

- Quick height adjustment.
- Handrails, platform stabiliser bars, ground stabilisers are all integrated into the structure.

MANY APPLICATIONS



- Telescopic mechanism allows 7 working heights from 2.33 to 4 m to suit many applications.
- The Podium platform can be set at two working heights (2.33 m and 2.61 m) to work in spaces with low ceilings.



Working height 4 m



Working height 3 m with Duaribag option

TELETOWER

— LENGTH : 1,50 M
Max working height : 4 m



COMFORT AND SAFETY ENSURED



- The large aluminium platform (1.40 x 0.60m) provides secure and comfortable work area.

A trapdoor
Aluminium toeboards.



- 4 Integral, multi-position stabilisers, adjustable for uneven ground



- The teletower is erected safely from the ground level.



7 WORKING HEIGHTS



HIGH
VERSATILITY



TECHNICAL DATA	TELETOWER
Safety★	Compliant to French regulation - Decree 2004-924
Material	Anodised aluminium
Max working height	4.00 m
Number of working height	7
Adjustment	Every 25 cm
Dimensions	1.50 x 0.80 m
Max overall dimensions	1.55 x 0.92 m
Folded dimensions	Height 1.10 m - Width 0.80 m - Thickness 0.45 m
Usable work zone on the platform	1.40 x 0.60 m
Safe working load	150 kg
Total weight	58 kg
Castors diameter	100 mm
Uprights diameter	Min. 44 mm to Max. 68 mm