
(M) wheelys

PATENT

### **A NEW GENERATION OF PLATFORM** PENDING **ULTRA EASY TO MOVE**

Between your aisles or on your building sites

Thanks to the presence of its 4 swivel castors, the Wheelys will thread its way anywhere with great ease.



Under the weight of the operator, the platform stands firmly and securely thanks to its slip-resistant feet.



## AVAILABLE IN 3 AND 4 STEPS to meet all needs.



Wheelys 4

Wheelys **3 steps** Working height **2.70 m** 2004-924 ORDER STANDARD EN 131-7 STANDARD PIRL



# 



## A NEW GENERATION OF PLATFORM



## UNFOLDS In a single Movement...



## FLUID FLOW

from the fully **unfolded platform**, on **construction sites**, in **factories** or **between aisles** 



#### Under the weight\* of the operator, the platform stands firmly and securely thanks to its slip-resistant feet. \*Weight 50 kg mini.



From the moment **the operator mounts the platform**, his weight **automatically disengages the castors**, ensuring the firm and stable standing of the platform.



## **SERENE HEIGHT**

The feeling of **comfort** and **safety** for the operative is immediate, **with a 360° protection** on an **ultra stable** platform.



## **EVERYTHING CLOSE AT HAND**

#### **2 STANDARD TOOL TRAYS**

- A **top tray** for small tools and miscellaneous supplies.
- A **broad low tray** for materials and goods. Capacity 25 kg.



TECHNICAL SPECIFICATIONS	WHEELYS 3	WHEELYS 4	
Safety * *	Decree of 01/09/2004	Decree of 01/09/2004	
	EN131-7 STANDARD AND IORL 🔊	EN131-7 STANDARD	
Material	Aluminium	Aluminium	
Number of treads	3	4	
Non-slip treads width (mm)	80	80	
Maximum working height (m)	2,70	2,95	
Floor height (m)	0,70	0,95	
Width (m)	0,75	0,79	
Folded dimensions (m) (L x W x Ep)	1,93 x 0,75 x 0,25	2,23 x 0,79 x 0,25	
Floor dimensions (m)	0,40 x 0,50	0,40 x 0,50	
Weight (kg)	20,9	21,5	
Duty rating	150	150	
Diameter of the 4 swivel castors (mm)	80	80	
Diameter of the 2 running wheels (mm)	100	100	

DIMENSIONS FOLDED SUPER REDUCED

> Presence of two running wheels (non-load bearing in the working position) for easy handling of the folded platform.

> > f) (in

www.duarib.fr





#### DUARIB - CDH GROUP

Route de la Limouzinière - BP 41 - 44 310 Saint-Philbert de Grand-Lieu Tél. : 02 40 78 97 22 - Télécopie service commercial : 02 40 78 80 45

www.duaric